

BAU-STR Dryer

Paddy Drying Technology



Dry Paddy in BAU-STR save time, labour and cost

Composition

Professor Dr. Md. Monjurul Alam
Professor Dr. Chayan Kumer Saha
Md. Ashraful Alam

Published By

USAID Post Harvest Loss Reduction Innovation Lab (PHLIL) - Bangladesh

Department of Farm Power and Machinery
Bangladesh Agricultural University, Mymensingh



Introduction

Bangladesh is an agriculture based country and rice is staple food. At present Bangladesh is now producing about 55.5 million ton of paddy (FAO, 2014) to feed the growing population. Drying is the most important part after harvesting paddy. Sun drying is a traditional and common practice in Bangladesh where paddy is exposed to sun and wind in the yard or field. Paddy drying is difficult during rainy and cloudy day and causes huge losses. To solve this problem BAU-STR dryer is a low cost batch dryer. This dryer was improved by “USAID Post Harvest Loss Reduction Innovation Lab (PHLIL)”, Department of Farm Power and Machinery, Bangladesh Agricultural University.

Objectives

- Dry paddy in less time and low cost;
- High quality rice and seed marketing by reducing paddy moisture
- Reduce Post Harvest Loss
- Reduce Labour requirement and health risk

Description of BAU-STR dryer

A low cost BAU-STR dryer consists of a blower, inner bin, outer bin, hot air conveyor pipe and stove (chula). It also requires loading materials such as bricks or stone or soil clod, polythene sheet (covering material), bamboo and rope (binding material).



Blower

- It is an axial flow blower.
- Both diameter and height are 49 cm and operated by 1 hp (0.746 kW) motor
- RPM is 2874
- The average air flow rate of blower is 33.5 m/s



Inner bin

- Inner bin is made of two types of net (one is 18 meshes and another is 1 inch)
- Diameter is 40 cm and height is 113 cm



Outer bin

- Outer bin is made same as inner bin with two types of net (one is 18 meshes and another is 1 inch).
- Height of bin is 113 cm and diameter is 112 cm
- Outer bin is flexible to fix up depending on amount of available grain



4. Stove (Chula)

- Stove is made of iron sheet and mild steel rod with clay soil
- Diameter is 36 cm and Height is 40 cm



5. Steel pipe

- It is the pipe which conveys the hot air from stove (Chula) to inner bin of the dryer
- It has two parts which can adjust the desirable length
- Its diameter is about 9 cm
- The pipe is divided into two parts so that it can be adjustable
- One side of steel pipe is funnel type so that the hot air can easily conveyed by the stove to the inner bin.



Materials required during drying operation

- Rice husk briquette (about 1 inch piece)
- Diesel (diesel engine operated blower)



Installation of BAU-STR dryer

- At first, inner bin of BAU-STR dryer should be set up on a plain surface
- Then the outer bin should be set up such that the annular space of inner bin and outer bin remain same.
- Then the grain should be delivered in the annular space between the inner bin and outer bin.
- The paddy grains should be delivered in the annular space of the dryer in such a way so that equal paddy contained in all sides.
- The outer grain bin should be fixed up around the inner bin with the help of GI wire as per required volume of grain.
- The axial flow blower should be set up on the top of the inner bin of the dryer and a polythene cover use to protect hot air leaking from the paddy of the dryer.
- A stove should place 2/1 feet high in one side of the grain bin and firing occur by using rice husk briquette.
- A steel pipe has to be set in one side of stove and other side in axial flow blower for hot air flow from the stove.
- The rice husk briquette should fill one third of stove and fire carefully. For proper heat production, rice husk briquette must be given into the stove every 4-5 minutes.
- After proper fire up, electricity or diesel engine should be started for running the blower.
- Temperature of hot air blowing to paddy bin needs to be monitored for maintaining paddy quality. Temperature should not exceed 43°C and this temperature can be maintained by controlling supply of rice husk briquette.

Cost of BAU-STR dryer

The Price of BAU-STR dryer is approximately 40,000 BDT to 60000 BDT.

Performance of BAU-STR dryer

- BAU-STR dryer can be made easily in local workshop
- Simple trained women and men can run the dryer
- 500 kg paddy can be dried in each batch in 4 to 5 hours
- 2 to 3% moisture can be reduced per hour
- 0.6 litre diesel is required if the blower is run by diesel generator.
- Drying efficiency is 65 to 70%

Economic parameter

- Three batch paddy (500 kg each batch) can be dried in a day
- Drying cost is 0.74 TK (if the blower is run by electricity from national grid) and 0.87 Tk (if the blower is run by diesel generator).

Conclusion

- Rice husk briquette is used for producing hot air, therefore, there is no smoke.
- BAU-STR dryer has excellent drying ability of paddy in adverse conditions, especially in depressions, heavy rain and cloudy days with low ambient air temperature and very high relative humidity
- Seed germination is more than 90%
- Rice quality is very good
- environmental friendly and characteristics of reducing health hazard of laborers

Precautions

In case of seed drying, fuel (rice husk briquette) supply should be controlled to minimize temperature below 43 °C. Firing should be continuous for uniform flow of hot air and ambient air mixer. Clean paddy should be used for drying to get maximum efficiency of dryer. Four to five hours tempering period should be maintained to get better quality of head rice recovery.

Contact Information

Professor Dr. Chayan Kumer Saha
Principal Investigator, Drying component

USAID Post Harvest Reduction Innovation Lab (PHLIL)-Bangladesh
Department of Farm Power and Machinery
Bangladesh Agricultural University
Mymensingh-2202, Bangladesh
Tel: +88 091 67401-6, 66016-18 Ext. 6841 Cell: +88 01715626517; Fax: +88 091 61510
Email: cksaha@bau.edu.bd; cksahabau@yahoo.com
Web: http://www.bau.edu.bd/pages/faculty_list/FPM

Professor Dr. Md. Monjurul Alam

In-Country Coordinator
USAID Post Harvest Reduction Innovation Lab (PHLIL)-Bangladesh
Department of Farm Power and Machinery
Bangladesh Agricultural University
Mymensingh-2202, Bangladesh
Email: mmalam.bau@gmail.com